



FIELDS OF USE


- Long lifetime
- Resistant to deep discharge
- Made from specially designed plate and active material
- Special grid alloy and minimum possible internal resistance

- Automatically Guided Vehicles (AGV)
- Ground Support Equipment (GSE)
- Fun Trains
- Cleaning Machinery
- Lifting Platforms
- Industrial Lifting Vehicles
- Golf Vehicles

FFP FLAT-PLATE FLOODED LONG-LIFE DEEP CYCLE BATTERIES

Code	Design Number	Voltage [V]	Capacity [Ah]	Box Type	CCA [A(EN)]	Weight ± 3 [Kg]	Dimensions L/W/h (mm)	Capacity (Ah)				Term. Type
								C20	C10	C5	C3	
YFFP6-225	27252055E	6	225	GU		31,5	261/181/252-274	225	207	185	149,1	A-S

Electrolyte Type	Liquid
Discharge Break Voltage at D.O.D.	1,80 VDC @ (A) $\leq 0,2C$
Storage Period1	6 months @ 25 °C
Self-Discharge	5% to %15 per month depending on storage temperature
Cell Float Voltage(VDC @ 25 °C)	2,25
Cell Cycle Voltage (VDC @ 25 °C)	2,43
Balancing Cell Voltage (VDC @ 25 °C)	2,55



 **Terminal Type A**
DIN 72311-4 Round Type

 **Terminal Type S**
(M-8 Optional)

